

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (cancelled)

Claim 2 (cancelled)

Claim 3 (currently amended) A photonic switch as ~~claimed in claim 2~~ for a DWDM network comprising:

a plurality I of input ports and a plurality I' of output ports;

al an optical demultiplexer for separating a wavelength λ_k from an input multichannel signal $S_{in}(k,i)$ received on an input port i of said plurality of input ports, and directing said wavelength λ_k on an assigned ingress area along a predetermined input path;

a switching block for directing said wavelength λ_k along an optical path from said assigned ingress area to an associated egress area selected from a plurality of egress areas;

an optical multiplexer for directing said wavelength λ_k from said associated egress area along a predetermined output path, and combining said wavelength λ_k into an output multichannel signal $S_{out}(k',i')$, transmitted on an output port i' of said plurality of output ports;

wherein said switching block comprises a switch fabric for cross-connecting said wavelength λ_k from said input multichannel signal $S_{in}(k,i)$ to said output multichannel signal $S_{out}(k',i')$ and a control unit for selecting said associated egress area and

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

configuring said switch fabric to direct said wavelength along an adaptable path between said assigned ingress area and said associated egress area and

a |
wherein said switch fabric comprises an input matrix with K rows and I columns of input optical switching elements, and an output matrix with K' rows and I' columns of output optical switching elements; wherein each input port of said plurality of input ports is associated with a column of said input matrix and each wavelength arriving on said each input port is associated with a row of said input matrix, and wherein each said output port of said plurality of output ports is associated with a column of said output matrix and each wavelength transmitted at each said output port is associated with a row of said output matrix and wherein said adaptable path transits said switch fabric such that an input optical switching element of said input matrix redirects said wavelength away from the plane of said input matrix to an output optical switching element of said output matrix.

Claim 4 (original) A photonic switch as claimed in claim 3, wherein said switching elements have minimum four degrees of freedom of orientation.

Claim 5 (original) A photonic switch as claimed in claim 3, wherein said switching elements are 3-D MEMS mirrors.

Claim 6 (original) A photonic switch as claimed in claim 3, wherein said optical demultiplexer and said input ports are arranged in a predetermined position relative to each other along said predetermined input path, for separating each input multichannel signal into component wavelengths according an area of incidence of said input multichannel signal on said demultiplexer.

Claim 7 (original) A photonic switch as claimed in claim 6, wherein said demultiplexer and said input matrix are arranged in a predetermined position relative to each other

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

along said predetermined input path, for directing each said component wavelength from said demultiplexer to said input matrix according to said wavelength λ_k and said input port i .

Claim 8 (cancelled)

Claim 9 (original) A photonic switch as claimed in claim 3, wherein said multiplexer and said output ports are arranged in a predetermined position relative to each other along said predetermined output path, for combining all wavelengths arriving in a certain area of incidence on said multiplexer within an output multichannel signal.

91
Claim 10 (original) A photonic switch as claimed in claim 9, wherein said demultiplexer and said output matrix are arranged in a predetermined position relative to each other along said predetermined output path, for directing each said wavelength λ_k from said output matrix to said certain area of incidence according to said wavelength λ_k and said input port i .

Claim 11 (original) A photonic switch as claimed in claim 10, further comprising optical elements arranged along said second predetermined path for directing said wavelength from said egress area on said associated output port.

Claim 12 (currently amended): A photonic switch as claimed in claim ~~[[2]]~~ 3, wherein $l=l'$ and $i=i'$.

Claim 13 (currently amended): A photonic switch as claimed in claim ~~[[2]]~~ 3, wherein $K=K'$, $k=k'$; $l=l'$ and $i=i'$.

Claim 14 (currently amended) A photonic switch as claimed in claim ~~[[1]]~~ 3, wherein said ~~switching block comprises~~ a switch fabric further comprises an add zone for cross-connecting said wavelength λ_k from said input multichannel signal $S_{in}(k,i)$ to said output

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

~~multichannel signal $S_{out}(k',i')$ and for cross-connecting an add wavelength incident on~~
said add zone to said output multichannel signal; and

~~a said control unit further capable of for configuring said switch fabric to direct~~
~~said wavelength along an adaptable path between said assigned ingress area and said~~
~~associated egress area, and configuring said switch fabric to direct said add wavelength~~
along an adaptable add path between said add zone and said associated egress area.

Claim 15 (original) A photonic switch as claimed in claim 14, further comprising a plurality of add ports.

91
Claim 16 (currently amended) A photonic switch as claimed in claim 15,

~~wherein said switch fabric comprises an input matrix with an input switching zone~~
~~of K rows and L columns of input optical switching elements and further comprises an~~
add zone of M rows and N columns of input optical switching elements, ~~wherein each~~
~~input port is associated with a column of said switching zone and each wavelength is~~
~~associated with a row of said switching zone, and wherein each add port of said~~
plurality of add ports is associated with a column of said add zone and each wavelength
arriving on said each add port is associated with a row of said add zone.

Claim 17 (currently amended) A photonic switch as claimed in claim ~~[[1]]~~ 3, further
comprising at least one drop port,

~~wherein said switching block comprises: a switch fabric further comprises a drop zone~~
~~for cross-connecting said wavelength λ_k from said input multichannel signal $S_{in}(k,i)$ to~~
~~said output multichannel signal $S_{out}(k',i')$ and for cross-connecting a drop wavelength~~
from said input multichannel signal on said drop zone; and

~~a control unit for configuring said switch fabric to direct said wavelength along an~~
~~adaptable path between said assigned ingress area and said associated egress area~~

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

~~and for directing~~ said drop wavelength along an adaptable drop path between said assigned ingress area and said drop zone.

Claim 18 (currently amended) A photonic switch as claimed in claim ~~[[1]]~~ 17, further comprising a plurality of drop ports.

91
Claim 19 (currently amended) A photonic switch as claimed in claim 18, wherein said switch fabric further comprises ~~an output matrix with K' rows and L' columns of output optical switching elements and a drop zone of M' rows and N' columns of output optical switching elements, wherein each said output port is associated with a column of said switching zone and each said wavelength is associated with a row of said switching zone, and wherein each drop port of said at plurality of drop ports is~~ associated with a column of said drop zone and each wavelength arriving on said each drop port is associated with a row of said drop zone.

Claim 20 (currently amended) A method of routing a wavelength within a photonic switch of a DWDM network, comprising:

pre-establishing an input optical path between an input port associated with said wavelength and an assigned optical switching element of an input matrix, according to a connectivity map;

establishing an adaptable path from said assigned optical switching element to an associated optical switching element of an output matrix wherein said adaptable path transits said switch fabric such that an input optical switching element of said input matrix redirects said wavelength away from the plane of said input matrix to an output optical switching element of said output matrix; and

pre-establishing an output optical path between said associated optical switching element and an output port of interest according to said connectivity map.

Claim 21 (original) A method as claimed in claim 20, further comprising

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

transiting said adaptable route to connect said assigned optical switching element to another optical switching element of said output matrix, whenever said connectivity map changes.

Claim 22 (currently amended) A photonic switch for routing a plurality of wavelengths of a DWDM transport network, between a plurality of input ports and a plurality of output ports comprising:

an all-optical switch fabric for cross-connecting a wavelength λ_k from an optical input multichannel signal $S_{in}(k,i)$ to an optical output multichannel signal $S_{out}(k',i')$, along an adaptable optical path; and

a control unit for configuring said adaptable optical path;

an optical demultiplexer for separating said wavelength λ_k from said optical input multichannel signal $S_{in}(k,i)$ and directing said wavelength λ_k on an assigned ingress area of said all-optical switch fabric along a predetermined input path; and

an optical multiplexer for receiving said wavelength λ_k received along a predetermined output path from an associated egress area of said all-optical switch fabric, and combining said wavelength λ_k with said optical output multichannel signal $S_{out}(k',i')$;

wherein said all optical switch fabric comprises an input matrix of K rows and I columns of optical switching elements, and an output matrix with K' rows and I' columns of output optical switching elements,

wherein said adaptable path transits said all optical switch fabric such that an input optical switching element of said input matrix redirects said wavelength away from the plane of said input matrix to an output optical switching element of said output matrix;

wherein each input port of said plurality of input ports is associated with a column of said input matrix, and each wavelength of said plurality of wavelengths is associated

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

with a row of said input matrix; and

wherein each output port of said plurality of output ports is associated with a column of said output matrix and each wavelength of said plurality of wavelengths is associated with a row of said output matrix.

Claim 23 (cancelled)

Claim 24 (cancelled)

Claim 25 (cancelled)

Claim 26 (cancelled)

91
Claim 27 (currently amended) A photonic switch as claimed in claim 22, further comprising an add port, and

wherein said all optical switch fabric comprises

~~an input matrix with a switching zone of K rows and I columns of optical switching elements, and~~

an add zone of M rows and N columns of input optical switching elements,
~~wherein each input port is associated with a column of said input matrix, and each wavelength is associated with a row of said input matrix, and~~

wherein each said add port is associated with a column of said add zone and each wavelength arriving on said add port is associated with a row of said add zone.

Claim 28 (cancelled)

Claim 29 (currently amended) A photonic switch as claimed in claim 22, further comprising a drop port wherein said switch fabric comprises

~~an output matrix with a switching zone of K' rows and I' columns of optical switching elements, and~~

Appl. No. 09/584,363
Amendment Dated March 5, 2004
Reply to Office Action of December 5, 2003

Our File: 38898-0089 TLS

a drop zone of M' rows and N' columns of optical switching elements, ~~wherein each said output port is associated with a column of said switching zone and each said wavelength is associated with a row of said output matrix, and~~

wherein each said drop port is associated with a column of said drop zone and each wavelength arriving on said drop port is associated with a row of said drop zone.

91
Claim 30 (original) A photonic switch as claimed in claim 3, wherein said input and said output matrices are arranged in two different planes.

Claim 31 (original) A photonic switch as claimed in claim 30, wherein said planes are substantially parallel to each-other.

Claim 32 (original) A photonic switch as claimed in claim 3 wherein said input and output matrices are arranged substantially in the same plane and wherein said switch block further comprises directing means arranged in the path of the light between said input and output matrices.
